

Harvest the Sunshine


545W



JA SOLAR

JAM60D42 LB n-type Double Glass Bifacial Modules

Premium Cells



MBB Half-Cell Technology

26%



Cell Conversion Efficiency

Premium Modules



Higher power generation better LCOE




n-type with very Lower LID



Better Temperature Coefficient



Better low irradiance response



12-year product warranty



30-year linear power output warranty

Comprehensive Certificates


- IEC 61215, IEC 61730
- ISO 9001: 2015 Quality management systems
- ISO 14001: 2015 Environmental management systems
- ISO 45001: 2018 Occupational health and safety management systems
- IEC 62941: 2019 Terrestrial photovoltaic (PV) modules - Quality system for PV module manufacturing



DEEP BLUE 4.0 Pro

JAM60D42 LB

n-type Double Glass Bifacial Modules



MECHANICAL PARAMETERS

Cell	Mono
Weight	28.8kg
Dimensions	2063 × 1134mm × 30mm
Cable Cross Section Size	4mm ² (IEC), 12 AWG(UL)
No. of cells	120(6 × 20)
Junction Box	IP68, 3diodes
Connector	QC Solar QC4.10-351/QC4.10-35 Stäubli PV-KST4-EVO2A/xy, PV-KBT4-EVO2A/xy
Cable Length (including Connector)	Portrait: 300mm(+)/400mm(-) Landscape: 1200mm(+)/1200mm(-)
Front Glass/Back Glass	2.0mm/2.0mm
Packaging Configuration	36pcs/Pallet, 792pcs/40HQ Container
Country of Manufacturer	China/Vietnam

Remark: customized frame color and cable length available upon request

ELECTRICAL PARAMETERS AT STC and BNPI

TYPE	JAM60D42 -520/LB		JAM60D42 -525/LB		JAM60D42 -530/LB		JAM60D42 -535/LB		JAM60D42 -540/LB		JAM60D42 -545/LB	
	STC	BNPI	STC	BNPI	STC	BNPI	STC	BNPI	STC	BNPI	STC	BNPI
Rated Maximum Power(P _{max}) [W]	520	570	525	575	530	585	535	590	540	595	545	602
Open Circuit Voltage (V _{oc}) [V]	43.53	43.53	43.73	43.73	43.93	43.93	44.13	44.13	44.33	44.33	44.53	44.53
Maximum Power Voltage(V _{mp}) [V]	36.37	36.37	36.59	36.59	36.81	36.81	37.03	37.03	37.25	37.25	37.46	37.46
Short Circuit Current(I _{sc}) [A]	15.16	16.61	15.21	16.66	15.26	16.84	15.31	16.88	15.36	16.92	15.41	17.01
Maximum Power Current(I _{mp}) [A]	14.30	15.68	14.35	15.72	14.40	15.90	14.45	15.94	14.50	15.98	14.55	16.06
Module Efficiency [%]	22.2		22.4		22.7		22.9		23.1		23.3	
Short Circuit Current (I _{sc}) [A] at BSI	18.66		18.68		18.71		18.74		18.77		18.97	
Power Tolerance	0~+3%											
Temperature Coefficient of I _{sc} (α _{Isc})	+0.045%/°C											
Temperature Coefficient of V _{oc} (β _{Voc})	-0.250%/°C											
Temperature Coefficient of P _{max} (γ _{Pmp})	-0.290%/°C											
STC	Irradiance 1000W/m ² , cell temperature 25°C, AM1.5G											
BNPI	front Irradiance 1000W/m ² , rear Irradiance 135W/m ²											
BSI	front Irradiance 1000W/m ² , rear Irradiance 300W/m ²											


Remark: Electrical data in this catalog do not refer to a single module and they are not part of the offer.
They only serve for comparison among different module types.
Measurement tolerance at STC and BNPI: P_{max} ±3%, V_{oc} ±3% and I_{sc} ±5%.

ELECTRICAL CHARACTERISTICS WITH 10% Bifacial Gains

TYPE	JAM60D42 -520/LB	JAM60D42 -525/LB	JAM60D42 -530/LB	JAM60D42 -535/LB	JAM60D42 -540/LB	JAM60D42 -545/LB
Rated Max Power(P _{max}) [W]	572.0	577.5	583.0	590	595	599.5
Open Circuit Voltage(V _{oc}) [V]	43.53	43.73	43.93	44.13	44.33	44.53
Max Power Voltage(V _{mp}) [V]	36.37	36.59	36.81	37.03	37.25	37.46
Short Circuit Current(I _{sc}) [A]	16.68	16.73	16.79	16.84	16.90	16.95
Max Power Current(I _{mp}) [A]	15.73	15.79	15.84	15.90	15.95	16.01

* For NextTracker installations, maximum static load please take compatibility approve letter between JA Solar and NextTracker for reference.

CHARACTERISTICS



OPERATING CONDITIONS

Maximum System Voltage	1500V DC
Operating Temperature	-40°C~+85°C
Maximum Series Fuse Rating	30A
Maximum Static Load, Front	3600Pa, 1.5
Maximum Static Load, Back	1600Pa, 1.5
NOCT	45 ± 2°C
Bifaciality	φP _{max} (80 ± 10) %, φV _{oc} (98 ± 5) %, φI _{sc} (80 ± 10) %
Safety Class	Class II
Fire Safety Class	Class C



Headquarters

JA Solar Technology Co., Ltd.
No. 123 Xinxing Road, 055550 Ningjin County, Hebei Province,
PEOPLE'S REPUBLIC OF CHINA

Specifications subject to technical changes and tests.
JA Solar reserves the right of final interpretation.

Version No. : Aus-EN-20250109A