
Matrix clay and concrete roofing tiles:
Compatible roof hooks

	Identifying feature	Processing	Notes	Types tiles / roof stones	SingleHook 3S/4S/3S Light SingleHook 3S long	SolidHook 3S+/4S+	SingleHook 2	SingleHook 1.1	SingleHook Alpin Metal roof plate or metal replacement tile required!	SingleHook FlatTile Metal replacement tile 2004282/2004440 required!	SingleHook Vario	SolidHook pantile	SolidHook Vario 1+2	SolidHook Flat Tile (plain tile single roofing)	SolidHook slate
Illustrations roof hooks					 2003215 / 2003144 / 2004795 / 2004222	 2002390 / 2002402	 2003175	 2001928	 2003155	 2004416	 2002651	 1000001 / 1000096 1001508 / 1000653 / 1000784	 1000125 / 1000107	 1000214	 1000373
Rail system					SingleRail	SolidRail	SingleRail	SingleRail	SingleRail	SingleRail	SingleRail	SolidRail	SolidRail	SolidRail	SolidRail
Clay roof tile	• Always 2 watercourses (left + top) • Rounded front edge, sharp-edged • Distance between battens very different and variable	Processing of the tiles at the lower and upper edge is always necessary.	Large overlap of the tiles possible, therefore note the boom length (T) of the roof hook; see pitched roof brochure "Overview of roof fastenings".		●	●	○	●	◉	○	●	●	●	○	○
					●	●	○	●	◉	○	●	●	●	○	○
Concrete roof tile	• Only a lateral watercourse • Visible concrete structure on the front side • Usually approx. 30 cm wide and approx. 42 cm long • L_A = Distance between battens approx. 31.5 - 34.5 cm	Processing of the tiles at the lower edge is always necessary – except when using the SingleHook 2 on flat concrete block			○	○	●	○	○	○	●	●	●	○	○
					●	●	○	●	◉	○	●	●	●	○	○
Plain tiles	• Scaled optics • Same dimensions (approx. 18 × 38 cm)		Distance between battens: approx. 15 - 17 cm		○	○	○	○	○	●	○	○	○	●	○









● Suitable ◉ Suitable with metal replacement tile ● Conditionally suitable Possibly increased installation effort - trial installation recommended ○ Unsuitable