SolarEdge EV Charger

For United Kingdom

SE-EVK74C00-01 / SE-EVK22URM-01

SMART ENERGY



Residential EV charging solution that seamlessly integrates with the full SolarEdge Home ecosystem

- Utilizes excess PV to charge EV from the sun, for reduced homeowner electricity bills
- Charge smarter with our custom scheduling feature, allowing automatic charging during low-rate periods, including at night or during a power outage
- Suitable for single and three phase installations, for both indoor and outdoor use
- Control and monitoring via the mySolarEdge app, including remote operations, charging schedules, and charging history
- G-100 compliant
- Tamper protected – designed to detect and alert about any tamper attempts
- Integrated optional RFID card authentication and MID meter*

* Only available in SolarEdge EV Charger for Three Phase systems, PN SE-EVK22URM-01.

SolarEdge EV Charger

For United Kingdom

SE-EVK74C00-01 / SE-EVK22URM-01

		SE-EVK74C00-01	SE-EVK22URM-01	
SPECIFICATIONS				
Rated AC Power Output		Up to 7.4kW	Single Phase: Up to 7.4kW Three Phase: Up to 22kW	kW
Rated Current (configurable)		Single Phase: 10 / 13 / 16 / 20 / 25 / 32	Single Phase and Three Phase: 10 / 13 / 16 / 20 / 25 / 32	A
Nominal AC Output Voltage		230	3 x 230 / 400	V
Line Frequency		50		Hz
Mains Forms		TT / TN / IT		
Internal Consumption		Idle: 4; plugged in: 5; charging: 7		W
Charge Mode		Mode 3 in accordance with IEC 61851-1 AC charging		
Over-Voltage Category		III, in accordance with EN 60664		
Protection Class		IP54		
Protection Against Mechanical Impact		IK10		
Rated Short-Circuit Current		< 10 (effective value in accordance with EN 61439-1)		kA
Residual Direct Current Detecting Device (RDC-DD)		> 6 (characteristic in accordance with IEC 62955, < 10 s)		mA
Ventilation		No		
Compatible Inverters		All SetApp-enabled residential inverters up to SE15K, excluding the Single Phase Inverter with Compact Technology		
Maximum Device Pairing Capacity		1		
AC TERMINALS				
Cable Feed		Top (surface); back side (flush)		
Type		Spring-type terminal		
Cross-section	Rigid / flexible	0.2 – 16		mm^2
	Flexible with wire end sleeve with / without plastic sleeve	0.25 – 10		mm^2
Stripping Length		12		mm
Connection Cross-section of the Supply		Suggested minimum cross-section:		
	16 A rated current	5 x 2.5		mm^2
	32 A nominal current	5 x 6.0		mm^2
Temperature Rating		105		°C
CABLE / SOCKET				
Type		Type 2: up to 32 A / 400 V AC in accordance with EN 62196-1 and VDE-AR-E 2623-2-2		
Cable Length (for variants with cable)		6		m
AMBIENT CONDITIONS				
Installation Environment		Indoor and outdoor		
Operating Temperature @16 A		-25 to +50 (without direct sunlight)		°C
Operating Temperature @32 A		-25 to +40 (without direct sunlight)		°C
Storage Temperature		-25 to +80		°C
Relative Air Humidity		5 to 95 (non-condensing)		%
Altitude		Max. 2000 above sea level		m
COMMUNICATION INTERFACE				
Ethernet 1		LSA+® terminals		
Data Transfer Rate		10 / 100		Mbit/s
Ethernet 2		RJ45 alternative to Ethernet 1		
WLAN/WI-FI		IEEE 802.11 b,g,n, 2.4 GHz		
WLAN/WI-FI Supported Modes		AP Ad-hoc-Mode, Client Mode Frequency 2400-2483.5 MHz, EIRP ≤ 20 dBm		
ADDITIONAL CAPABILITIES				
RFID Card		MIFARE card /tag according to ISO 14443 or ISO 15693 Frequency 13.553-13.567 MHz, EIRP ≤ -7 dBm		
OCPP Backend		SolarEdge OCPP pre-configured		
Tamper Protection		SolarEdge Tampering Alert System		
STANDARD COMPLIANCE				
UKCA		Yes		
MID		-	Accuracy Class B (according to EN 50470-1 /-3, CE)	
G100 Issue 2 Amendment 2		Yes, with SolarEdge PV inverter(1) and Energy Meter or Backup Interface		
DIMENSIONS AND WEIGHT				
Height (Cable / Socket) X Width X Depth		643 / 495 X 240 X 142		mm
Weight (Cable / Socket)		7.8 / 5		kg

(1) All SetApp-enabled residential inverters up to SE15K, excluding the Single Phase Inverter with Compact Technology.

ORDERING INFORMATION	
PART NUMBER	**DESCRIPTION**
SE-EVK74C00-01	SolarEdge EV Charger, 7.4 kW, 1 phase, 6m Cable, Type 2, UKCA
SE-EVK22URM-01	SolarEdge EV Charger, 22 kw, Socket, RFID, MID, UKCA

© SolarEdge Technologies, Ltd. All rights reserved. SOLAREDGE, the SolarEdge logo, OPTIMIZED BY SOLAREDGE are trademarks or registered trademarks of SolarEdge Technologies, Inc.
All other trademarks mentioned herein are trademarks of their respective owners. Date: November 16, 2023 DS-000191-UK. Subject to change without notice.