Easee Base

Easee Base is a durable, weatherproof post for flexible charger placement – perfect when wall mounting isn't possible. With a built-in Power Rail, each post supports up to four chargers and can be linked with additional Bases in series.

Flexible. Durable. Scalable.

Why choose Easee Base?

Benefits

- Supports up to four chargers on a single post.
- Available in 1-way, 2-way and 4-way kit configurations.
- Power Rail integration for simple wiring and series connection of multiple Bases.
- Durable aluminium and stainless steel with scratch-resistant coating.
- Clean, minimalist design that blends seamlessly with the Easee chargers.
- Integrated hooks[1] for cable arrangement.
- 45° adapter plate for flexible alignment, ideal for uneven foundations or angled placement
- Designed and manufactured in Norway.

[1] Only available for 1-way and 2-way setups. The charging cable can be permanently locked in the Easee Charger.



Integrated Power Rail

The Easee Base kits includes a Power Rail that connects all chargers on the post and allows multiple Bases to be linked in series - using a single power cable.

This reduces installation time, minimises cabling and provides a clean, scalable setup – suitable for both single installations and larger sites.

Whether you're installing one charger or managing an entire parking area, the Power Rail supports a future-proof and professional setup.



Easee Base Kits

Concept

Easee Base consists of two parts. This modular design simplifies installation and lets you configure the setup you need.

Part 1: Easee Base Column

The aluminium and stainless steel column houses the Power Rail for simple installation and clean cable management.

Part 2: Easee Base Kits

The Base Kits include the components needed for your chosen setup and define how many chargers can be mounted on the column. Kits are available in 1-way, 2-way and 4-way configurations.

Configurations

Column + 1-Way



Column + 2-Way

Column + 4-Way

Specifications

Measurement
in mm



1-way / 2-way

4-way



Adapter plate



Post base plate

Technical

General

Dimension (mm):
1-way / 2-way: H: 1170 x W: 160 x D: 80.
4-way: H: 1170 x W: 186 x D: 186.
Mounting plate (mm):
H: 380 x W: 160 x D: 45.
Charging socket-outlet height (mm): 950.
Weight: 6.1–7.7 kg.
Material: Aluminium and stainless steel (adapter plate/ mounting plate).
Finish: Powder coating.
Colour: Black.
IP degree: IP44.
Insulation class: I (with Power Rail).
Impact resistance: IK10.

Features

Adapter plate for c/c 160 mm^2 foundation.
45 degree rotation intervals (using the adapter plate).
Screws and nuts included.
Adapter plate supports 22 mm bolts.

Electrical connection

Connection via Power Rail (optional) requires the circuit to be RCD protected. Multiple charging posts can be connected in series.

Power Rail cable size

Maximum support of 16mm^2 flexible conductors with ferrules and 25mm^2 solid conductors.
Cable length between Power Rail and chargers: 135 cm.
Conductor material: CU or ALU.

The Easee Base is delivered without the Easee Charger(s)

Column
Art. nr.: 92000

Column

Side panel

End cap

1-Way
Art. nr.: 92001



Mounting plate

1-way cover

Power Rail + Ground connection plate



Adapter plate

2-Way
Art. nr.: 92002



Mounting plate



Mounting plate

Power Rail + Ground connection plate



Adapter plate

4-Way
Art. nr.: 92004



Top frame



Top plate

Power Rail + Ground connection plate



Adapter plate



Bottom frame



3-Way cover
Sold separately
Art. nr.: 90300

The information in this document is for information purposes only, is provided as is, and may be subject to change without notice. Easee®, including its subsidiaries, does not accept any liability for the correctness or completeness of the information and illustrations, and is not liable or responsible for your considerations, assessments, decisions or absence of such, or other use of the information in this document.

No part of this publication may be re-published, reproduced, transmitted or re-used in any other form, by any means or in any form, for your own or any third-party's use, unless otherwise agreed with Easee or its subsidiaries in writing. Any permitted use shall always be done in accordance with good practice and ensure that no harm may be caused to Easee or by misleading the consumer.

Easee and Easee products, product names, trademarks and slogans, whether registered or not, are Easee's intellectual property and may not be used without Easee's prior written permission. All other products and services mentioned may be trademarks or service marks of their respective owners.

The latest version of this publication can be downloaded at **http://easee.support**

January 2026 - Version 2.01
© 2026 by Easee®. All rights reserved.

Easee ASA
Vassbotnen 23
4033 Stavanger, Norway
Org.nr: 920 292 046

Easee is distributed and maintained by a network of qualified partners and resellers. Find more information and your local partner at:

www.easee.com