

# EPS BOX PRO -HC

THREE-PHASE



- PC, Robust metal enclosure IP65
- Applied to residential, commercial solar installations
- Compatible with AIO-H3/H3/H3 Smart/P3-S/H3 Pro/P3 Pro inverter
- Automatically switch to On-Grid/Off-Grid state



**MAX. INPUT  
CURRENT 63A**



**EASY  
INSTALLATION**



**IP65  
RATED**



**SAFETY**



[www.fox-ess.com](http://www.fox-ess.com)

## TECHNICAL SPECIFICATIONS

| MODEL                               | EPS BOX PRO-HC                    |
|-------------------------------------|-----------------------------------|
| UTILITY SUPPLY                      |                                   |
| Rated Voltage [VAC]                 | 220 / 380, 230 / 400, 3L / N / PE |
| Rated Frequency [Hz]                | 50 / 60                           |
| Max. Input Current (Per Phase) [A]  | 63                                |
| INVERTER GRID                       |                                   |
| Rated Voltage [VAC]                 | 220 / 380, 230 / 400, 3L / N / PE |
| Rated Frequency [Hz]                | 50 / 60                           |
| Max. Input Current (Per Phase) [A]  | 63                                |
| INVERTER EPS                        |                                   |
| Rated Voltage [VAC]                 | 220 / 380, 230 / 400, 3L / N / PE |
| Rated Frequency [Hz]                | 50 / 60                           |
| Max. Input Current (Per Phase) [A]  | 63                                |
| LOAD                                |                                   |
| Rated Voltage [VAC]                 | 220 / 380, 230 / 400, 3L / N / PE |
| Rated Frequency [Hz]                | 50 / 60                           |
| Max. Output Current (Per Phase) [A] | 63                                |
| COMMUNICATION INTERFACE             |                                   |
| RS-485                              | Meter                             |
| GENERAL DATA                        |                                   |
| Cooling Concept                     | Natural                           |
| Installation                        | Wall-mounted                      |
| Operating Temperature Range [°C]    | -25 ~ +60 (Derating at 45)        |
| Dimensions (W*H*D) [mm]             | 550 * 420 * 138.5                 |
| Dimensions of packing (W*H*D) [mm]  | 660 * 515 * 235                   |
| Net Weight [kg]                     | 17                                |
| Gross Weight [kg]                   | 18                                |
| Ingress Protection                  | IP65                              |