REC

SOLAR'S MOST TRUSTED

2026 · CELEBRATING 30 YEARS OF EXCELLENCE

REC ALPHA® PURE-RX

DATASHEET



PURE STRENGTH

55 MM HAIL RESISTANT[a]

+7000 PA / -4000 PA
WITH 4 POINT CLAMPING

+10000 PA / -6000 PA
WITH 6 POINT CLAMPING

460 - 485W
HETEROJUNCTION TECHNOLOGY

233 W/M²	POWER DENSITY
>92%	POWER IN YEAR 25
-0.24%/°C	TEMPERATURE COEFFICIENT OF P_{MAX}

PRODUCT · REC 25 YEAR ProTrust WARRANTY · PERFORMANCE · LABOR

ELIGIBLE

REC ALPHA® PURE-RX
DATASHEET

REC
SOLAR'S MOST TRUSTED

2026: CELEBRATING 30 YEARS OF EXCELLENCE

GENERAL DATA

Cell Type	88 half-cut bifacial REC heterojunction cells, with gapless technology
Glass	3.2 mm solar glass with anti-reflective surface treatment in accordance with EN12150
Backsheet	Highly resistant polymer (Black)
Frame	Anodized aluminum (Black)
Junction Box	4-part, 4 bypass diodes, IP68 rated, in accordance with IEC 62790:2020
Connectors	Stäubli MC4 PV-KBT4/KST4 (4 mm²) in accordance with IEC 62852:2014, IP68 only when connected
Cable	4 mm² solar cable, 1.50 m + 1.50 m in accordance with EN50618:2014
Dimensions	1728 x 1205 x 30 mm (2.08 m²)
Weight	22.7 kg
Origin	Made in Singapore

Measurements in mm [in]



Specifications subject to change without notice.

ELECTRICAL DATA

PRODUCT CODE*: RECxxxAA Pure-RX

STC						
Power Output - P_{MAX} (W_p)	460	465	470	475	480	485
Watt Class Sorting - (W)	0/+5 0/+10ϕ	0/+5	0/+5 0/+10ϕ	0/+5	0/+5	0/+5
Nominal Power Voltage - V_{MPP} (V)	54.9	55.2	55.4	55.5	55.6	55.7
Nominal Power Current - I_{MPP} (A)	8.38	8.43	8.49	8.56	8.64	8.71
Open Circuit Voltage - V_{OC} (V)	65.7	65.7	65.7	65.7	65.8	65.9
Short Circuit Current - I_{SC} (A)	8.88	8.91	8.95	9.00	9.05	9.11
Power Density (W/m²)	221	223	226	228	231	233
Panel Efficiency (%)	22.1	22.3	22.6	22.8	23.1	23.3
NMOT						
Power Output - P_{MAX} (W_p)	350	354	358	361	365	369
Nominal Power Voltage - V_{MPP} (V)	51.7	52.0	52.2	52.3	52.4	52.5
Nominal Power Current - I_{MPP} (A)	6.77	6.81	6.86	6.91	6.98	7.03
Open Circuit Voltage - V_{OC} (V)	61.9	61.9	61.9	61.9	62.0	62.1
Short Circuit Current - I_{SC} (A)	7.18	7.20	7.23	7.27	7.31	7.36

Values at standard test conditions (STC: air mass AM 1.5, irradiance 1000 W/m², temperature 25°C), based on a production spread with a tolerance of P_{MAX}, V_{OC} & I_{SC} ±3% within one watt class. Nominal module operating temperature (NMOT: air mass AM 1.5, irradiance 800 W/m², temperature 20°C, windspeed 1 m/s). * Where xxx indicates the nominal power class (P_{MAX}) at STC above.

ϕAvailable while stocks last

TEMPERATURE COEFFICIENTS*

P_{MAX} -0.24%/°C V_{OC} -0.24%/°C I_{SC} 0.04%/°C

*The temperature coefficients stated are linear values

MODULE RATINGS

Module Operating Temperature [T98]§	80°C
Min Environmental Temperature	-40°C
Nominal Module Operating Temperature	44 ± 2°C
Max Hail Rating¤	55 mm @ 33.9 m/s
System Voltage	1000 V
Max Series Fuse Rating	25 A
Max Reverse Current	25 A

§ 98th percentile operating temperature
¤Kiwa PVEL HSS test result

MAXIMUM TEST LOAD*

Front (4-Point)*	+7000 Pa (714 Kg/m²)
Rear (4-Point)*	-4000 Pa (408 Kg/m²)
Front (6-Point)**	+10000 Pa (1,020 Kg/m²)
Rear (6-Point)**	-6000 Pa (612 Kg/m²)

Design load = Test load / 1.5 (safety factor)

*IEC61730/UL61730 certified. Refer to installation manual.
**Internal testing. Refer to installation manual.

CERTIFICATIONS

ISO 14001; ISO9001; IEC45001; IEC62941	
IEC 61215:2021;IEC 61730:2023;UL 61730	
IEC 61730	Fire Class C
ISO 11925-2	Ignitability (EN 13501-1 Class E)
EN 13501-5	Roof Fire Performance (B_{ROOF} T2)
IEC 62716	Ammonia Resistance
IEC 61701	Salt Mist (SM6)
IEC 61215:2021	Hailstone (35 mm)
UL 61730	Fire Type 2
IEC TS 63126	Level 1

take-e-way
for an easy way
Take-e-way WEEE-compliant scheme

WARRANTY

	Standard	REC ProTrust	
Installed by an REC Certified Professional	No	Yes	Yes
System Size	All	<25 kW	25-500 kW
Product Warranty (yrs)	20	25	25
Power Warranty (yrs)	25	25	25
Labor Warranty (yrs)	0	25	10
Power in Year 1	98%	98%	98%
Annual Degradation	0.25%	0.25%	0.25%
Power in Year 25	92%	92%	92%

REC ProTrust Warranty applies only for i) REC panels installed by an REC Certified Solar Professional, and ii) panels have been registered by the installer with REC. Subject to System Size and further conditions. See www.recgroup.com for details.

DELIVERY INFORMATION

Panels per Pallet	33
Panels per 40 ft GP/high cube container	594 (18 Pallets)
Panels per 13.6 m truck	660 (20 Pallets)

LOW LIGHT BEHAVIOUR

Typical low irradiance performance of module at STC:



Available from:

Founded in 1996, REC Group is an international pioneering solar energy company dedicated to empowering consumers with clean, affordable solar power. As Solar's Most Trusted, REC is committed to high quality, innovation, and a low carbon footprint in the solar materials and solar panels it manufactures. Headquartered in Norway with operational headquarters in Singapore, REC also has regional hubs in North America, Europe, and Asia-Pacific.

REC Solar PTE. LTD.
20 Tuas South Ave. 14
Singapore 637312
post@recgroup.com
www.recgroup.com

REC

IEC EN 8.2026 V8 REF: PM-DS-12-06/09.04.08.01